

## ELECTRONIC CAPACITIVE DETECTOR OF VOLTAGE PRESENCE / ABSENCE ON MV LINES AND INSTALLATIONS BY VISUAL AND ACOUSTIC SIGNALLING

### TYPE **RMT 1030U-P3/600U-TEL**

**CERTIFIED IN CONFORMITY WITH THE INTERNATIONAL STANDARD CEI IEC 61243-1 Ed.2 2003-10.**



Voltage use: 11-33 kV.  
Suitable for use in wet condition, either indoors or outdoors.  
Double indications of operative voltage presence: intermittent acoustic and flashing of 2 red led-lights.  
The absence of operative voltage is indicated by green led-light permanent on.  
The lighting of the orange led-light is the indication of flat battery.  
**Built-in self control check** for testing the accurate working of the voltage detector before use.  
Box made by plastic material.  
Metallic contact probe V shaped.  
Attachment with universal splined end attack for connection onto the head of the insulating rod.  
Supply: alkaline battery 9 V.  
Supplied into a metallic case.



High insulating telescopic rod made by tubes made by polyester resin reinforced by fiberglass, white colour.  
Type **P3/600U-TEL**, extended length 6 m in 3 elements, composed by:

- base element external diameter 40 mm, length 2 m, with hand guard and lower cap;
- intermediate element external diameter 32 mm, length 2 m;
- upper element external diameter 24,3 mm, length 2 m, with universal splined end attack type **U** onto the head for fixing the voltage detector.

