



STAINLESS STEEL CABLE TIES & MARKERS

ROLLER BALL TYPE STAINLESS STEEL CABLE TIES

MATERIAL : STAINLESS STEEL GRADE 316/304

Features :

This roller ball design tie is self locking and is easy to install. Fixing can be done by hand, tool or both.

Specification :

Min. loop tensile strength - 4.6 mm width (44.5 kg) 100 lbs
Min. loop tensile strength - 7.9 mm width (113.6 kg) 250 lbs

Operating temperature :

-80°C to + 150°C (Coated)
-80°C to + 538°C (UnCoated)

Applications :

Construction, Automobile, Offshore, Petro-Chemical Industries, Fire protection, Aerospace, Flame Proof Installation etc.

Length (mm)	Width (mm)	Max. Bundle Dia. (mm)	Product Code
100	4.6	16	HH - 100
150	4.6	32	HH - 150
200	4.6	50	HH - 200
360	4.6	101	HH - 360
520	4.6	152	HH - 520
680	4.6	203	HH - 680
840	4.6	254	HH - 840
1000	4.6	298	HH - 1000
200	7.9	50	HH - 200 H
360	7.9	101	HH - 360 H
520	7.9	152	HH - 520 H
680	7.9	203	HH - 680 H
840	7.9	254	HH - 840 H
1000	7.9	298	HH - 1000 H

For coated version add Suffix 'CT' to product code.

(For example : CTHH100 for 100 mm length)

RELEASABLE TYPE STAINLESS STEEL CABLE TIES

MATERIAL : STAINLESS STEEL GRADE 316/304

Features :

These tie has greater flexibility as it can Fasten-Unfasten as per usage. Coated ties are used for added resistance to corrosion and weathering effect.

Operating Temperature

-80°C to + 150°C (Coated)

Length (mm)	Width (mm)	Max. Bundle Dia. (mm)	Product Code
150	5	36	HRT - 1505
230	5	60	HRT - 2305
330	5	95	HRT - 3305
450	5	130	HRT - 4505
150	10	36	HRT - 1501
230	10	60	HRT - 2301
330	10	95	HRT - 3301
450	10	130	HRT - 4501

For coated version add Suffix 'CT' to product code

(For example : CTHRT 1505 for 150 mm length)

