



ST-3600



ST-3602



ST-3620

FEATURES

- Display 3½ digit, liquid crystal display with maximum reading of 1999.
- Over range indication : "1" is displayed on highest digit.
- Low battery indication : "B" sign appears on the display.
- Response time : approx.1 second.
- Data hold : for all ranges

SPECIFICATIONS

Model	ST-3600	ST-3602 (Auto-Ranges)	ST-3620
ACA	200/1500 ±(2%rdg+4dgt) (40Hz-1KHz)	200/1500 ±(2%rdg+4dgt) (40Hz-1KHz)	200/1500 ±(2%rdg+4dgt) (40Hz-1KHz)
ACV	200/750 ±(1.5%rdg+2dgt) (40Hz-1KHz)	200/750 ±(1.5%rdg+2dgt) (40Hz-1KHz)	200/750 ±(1.5%rdg+2dgt) (40Hz-1KHz)
DCA	200/1500 ±(2%rdg+4dgt)	200/1500 ±(2%rdg+4dgt)	—
DCV	20/200/1000 ±(1%rdg+2dgt)	200/1000 ±(1%rdg+2dgt)	—
Ω	200/1500 ±(1.5%rdg+2dgt)	200/1500 ±(1.5%rdg+2dgt)	200 ±(1.5%rdg+2dgt)
Diode check	0-1500mV ±(1.5%rdg+2dgt)	0-1500mV ±(1.5%rdg+2dgt)	—
Buzzer	—	Resistance is less then 100Ω	Resistance is less then 30Ω
Peak Hold	—	—	V
Conductor Size	ø55mm Max.	ø55mm Max.	ø55mm Max.
Dimensions	245(L) x 70(W) x 41.7(D)mm	245(L) x 70(W) x 41.7(D)mm	245(L) x 70(W) x 41.7(D)mm
Power Source	9V(6F22) x 1	9V(6F22) x 1	9V(6F22) x 1
Weight (Battery Included)	480g Approx.	480g Approx.	480g Approx.
Operating Temperature	-10°C~50°C	-10°C~50°C	-10°C~50°C
Humidity	85%	85%	85%
Current Consumption	10mA Approx.	10mA Approx.	10mA Approx.
Accessories	Test leads (AL-26) Carrying case (CAC-3600) Instruction manual Battery	Test leads (AL-26) Carrying case (CAC-3600) Instruction manual Battery	Test leads (AL-26) Carrying case (CAC-3600) Instruction manual Battery

EMPIRE TRADING AGENCY
No. 110, LAYARDS BROADWAY,
COLOMBO 14.
TEL (GENERAL) : 011 2 433 047, 011 2 343 701
TEL (SALES) : 011 5 330 470 -71
FAX : +94-(0)11-2 431 180
E-MAIL : empita@slt.lk