

FEED THROUGH TERMINAL CONNECTORS (KUT - N Series)

MODEL NO	RATED CROSS SECTION	CONDUCTOR SIZE (sq.mm)		TERMINAL PITCH	HEIGHT x WIDTH in mm(inch)	WIRE STRIPPING LENGTH	RATINGS (V A)	IMAGE
		Flexible	Rigid					
KUT 2.5N	2.5 sq mm	0.5 - 2.5	0.5 - 4	5mm (0.20Inch)	51 x41.5 (2.00 x 1.63)	10mm	600 V/20 A, 12-20 AWG/6 Lbln	
KUT 4N	4 sq mm	0.5 - 4	0.5 - 4	6mm (0.24Inch)	51 x41.5 (2.00 x 1.63)	12mm	600 V/24 A, 12-20 AWG/6 Lbln	
KUT 6N	6 sq mm	0.5 - 6	0.5 - 10	8mm (0.31Inch)	51 x41.5 (2.00 x 1.63)	12mm	600 V/35 A, 8-20 AWG/13 Lbln	
KUT 10N	10 sq mm	1.5 - 10	1.5 - 16	10mm (0.40Inch)	51 x41.5 (2.00 x 1.63)	10mm	600 V/57 A, 6-16 AWG/14 Lbln	
KUT 16	16 sq mm	6 - 16	6 - 25	12mm (0.47Inch)	51 x44.5 (2.01 x 1.75)	15mm	600 V/76 A, 3-12AWG/17 Lbln	
KUT25	25 sq mm	6 - 25	6 - 25	12mm (0.47Inch)	56 x45 (2.2 x 1.77)	15mm	600 V/101 A, 2-10 AWG/20 Lbln	
KUT 35	35 sq mm	10 - 35	10 - 35	17mm (0.67Inch)	58 x51 (2.28 x 2.01)	17mm	600 V/135 A, 1-14 AWG/38 Lbln	
KUT 50	50 sq mm	16 - 50	16 - 70	20.5mm (0.81Inch)	75.5 x71 (2.97 x 2.8)	24mm	600 V/150 A, 2/0-6AWG/60 Lbln	
KUT 95	95 sq mm	25 - 95	25 - 120	25mm (0.98Inch)	90.5 x83 (3.56 x 3.27)	33mm	600 V/230 A, 4/0-2AWG/160 Lbln	

EARTH TERMINAL

ET 4	4 sq mm	0.5 - 4	0.5 - 4	6mm (0.23Inch)	36.0 x40 (1.41 x 1.57)	8mm	4 sq mm - 0.5Nm	
ET 6	6 sq mm	1.5 - 6	1.5 - 10	8mm (0.31Inch)	45.5 x43 (1.76 x 1.69)	13mm	6 sq mm - 0.8Nm	